

ET1 LLDPE POLYETHYLENE TUBING



ET1 is an LLDPE Polyethylene Tubing that is economical and lightweight, and stands up to environmental stress cracking and higher pressures. The chemically inert linear low density polyethylene is also a food grade material. It forms a good barrier to gases, vapors, and moisture, and is available up to 1-1/2" diameters. Applications include transfer of liquids and air for any number of industrial applications. -50F to 140F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	COIL LENGTH	WEIGHT
	(in)	(in)		(in)	(psi)	(feet)	(lbs/in)
	1/8			1/4	140	100	0.0147
	3/16			5/16	140	100	0.02
	1/4			3/8	125	100	0.025
	3/8			1/2	100	100	0.035
	1/2			5/8	75	100	0.044
	5/8			3/4	60	100	0.054
	3/4			1	50	100	0.054

NOTES: *THE HOSE IS RATED FOR 25 TO 150 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RATING. AVAILABLE IN METRIC SIZES.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 HOSECRAFT USA				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;">ET1</td> </tr> <tr> <td>DRAWN BY: PDB 8/04</td> <td style="text-align: center;">LLDPE POLYETHYLENE TUBING</td> </tr> </table>	MODEL:	ET1	DRAWN BY: PDB 8/04	LLDPE POLYETHYLENE TUBING
MODEL:	ET1				
DRAWN BY: PDB 8/04	LLDPE POLYETHYLENE TUBING				