

## FW1 WELD EXHAUST HOSE



STANDARD LENGTHS ARE 25 FEET.

The Model FW1 hose is designed for welding exhaust at high temperatures. It has a heavy duty 2-ply construction for extra durability. The outer aluminized fiberglass deflects heat, and the helix is corrosion resistant.

Compression ratio is 4:1.

Standard lengths are 25 feet.

Temperature range from -20F to 600F.

Contact factory for larger diameters, up to 24".

QTY	HOSE DIA	OAL	ENDS	PRESSURE	VACUUM	COMPRESSION RATIO	WEIGHT
	(in)	(in)		(psi)	(in Hg)		(lbs/ft)
	3			4.3	3.2	4:1	-
	4			4	2.7	4:1	-
	5			3.6	2.4	4:1	-
	6			3.5	2.2	4:1	1.34
	8			3	1.8	4:1	-
	10			2.15	1.6	4:1	-
	12			1.8	1.25	4:1	-

**NOTES:** THE HOSE IS RATED FOR -20F TO 600F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;"><b>FW1</b></td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;"><b>WELD EXHAUST HOSE</b></td> </tr> </table>	MODEL:	<b>FW1</b>	DRAWN BY:	<b>WELD EXHAUST HOSE</b>
MODEL:	<b>FW1</b>				
DRAWN BY:	<b>WELD EXHAUST HOSE</b>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">PDB 3/22/06</td> <td style="width: 50%;"></td> </tr> </table>	PDB 3/22/06			
PDB 3/22/06					