

LS1 PLASTIC SUCTION/DISCHARGE HOSE



CUFFS NOT SHOWN.

LS1 is a lightweight and crush-proof plastic suction and transfer hose that retains its excellent flexibility even in the cold weather. A smooth bore tube minimizes material buildup and is resistant to a variety of chemicals in sanitary and many other industrial and construction applications. The outer helix resists abrasion and allows for crush-proof and non-kinking usage. -

40F to 140F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	VAC	WEIGHT
	(in)	(in)		(in)	(psi)	(in hg)	(lbs/ft)
	1 1/2			2.17	20	29	0.6
	2			2.76	15	29	0.85
	2 1/2			3.42	10	29	1.25
	3			4.06	7	29	1.6
	4			5.62	5	29	3.3

NOTES: THE HOSE IS RATED FROM -40F TO 200F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____		MODEL:	LS1
DRAWN BY: PDB 1/1/04		PLASTIC SUCTION	

FLEXICRAFT INDUSTRIES 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 312-738-3588 FAX: 312-421-6327