

## MD1 ALUMINUM DUCT HOSE




The MD1 Aluminum Duct hose is helically corrugated for light weight and hand bendable applications that need to be self-supporting and stationary. Hose connectors available.

Comes in standard lengths of 10 feet, and up to 50 feet in 5 foot increments. ULC listing as Class 1 air duct. Temperature range -60 to 600F.

QTY	HOSE DIA	OAL	COMPR RATIO	BEND RADIUS	WEIGHT	PRES	VACUUM
	(in)	(FT)		(in)	(lbs/ft)	(in w.g.)	(in Hg)
	<b>2</b>		3:1	3	0.113	12	0.3
	<b>3</b>		3:1	4.5	0.167	12	0.3
	<b>4</b>		3:1	6	0.2	12	0.3
	<b>5</b>		3:1	7.5	0.25	12	0.3
	<b>6</b>		3:1	9	0.3	12	0.3
	<b>7</b>		3:1	10.5	0.35	12	0.3
	<b>8</b>		3:1	12	0.35	12	0.3
	<b>9</b>		3:1	13.5	0.4	12	0.3
	<b>10</b>		3:1	15	0.44	12	0.3
	<b>12</b>		3:1	18	0.53	12	0.3

**NOTES:** THE HOSE IS RATED FOR 600 DEG F. RATED VELOCITY IS 4000 F/M  
MODEL MD2 AVAILABLE IN 316 STAINLESS STEEL.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;"><b>MD1</b></td> </tr> <tr> <td>DRAWN BY: PDB 1/1/04</td> <td style="text-align: center;"><b>ALUMINUM DUCT HOSE</b></td> </tr> </table>	MODEL:	<b>MD1</b>	DRAWN BY: PDB 1/1/04	<b>ALUMINUM DUCT HOSE</b>
MODEL:	<b>MD1</b>				
DRAWN BY: PDB 1/1/04	<b>ALUMINUM DUCT HOSE</b>				