

MD2 STAINLESS STEEL DUCT HOSE



The MD2 316 Stainless Steel Duct hose is helically corrugated for light weight and hand bendable applications that need to be self-supporting and stationary. A .005" wall thickness that has a four ply finished seam, folded flat and crimped. Hose connectors available.

Comes in standard lengths of 10 feet, and up to 50 feet in 5 foot increments. ULC listed as Class 1 air duct. Temperature range -60 to 1700F.

QTY	HOSE DIA	OAL	COMPR RATIO	BEND RADIUS	WEIGHT	PRES	VACUUM
	(in)	(FT)		(in)	(lbs/ft)	(in w.g.)	(in Hg)
	2		3:1	3	0.17	12	0.3
	3		3:1	4.5	0.31	12	0.3
	4		3:1	6	0.35	12	0.3
	5		3:1	7.5	0.45	12	0.3
	6		3:1	9	0.54	12	0.3
	7		3:1	10.5	0.62	12	0.3
	8		3:1	12	0.64	12	0.3
	10		3:1	15	0.8	12	0.3
	12		3:1	18	0.95	12	0.3

NOTES: THE HOSE IS RATED FOR 1700 DEG F. RATED VELOCITY IS 4000 F/M.
MODEL MD1 AVAILABLE IN ALUMINUM.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;">MD2</td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;">316 STAINLESS STEEL DUCT HOSE</td> </tr> </table>	MODEL:	MD2	DRAWN BY:	316 STAINLESS STEEL DUCT HOSE
MODEL:	MD2				
DRAWN BY:	316 STAINLESS STEEL DUCT HOSE				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">PDB 1/1/04</td> <td></td> </tr> </table>	PDB 1/1/04			
PDB 1/1/04					