

## PD2 PVC HEAVY DUTY DISCHARGE HOSE




The Model PD2 is a red PVC discharge lay-flat hose that resists kinking and twisting for use at higher pressures. It is designed as a heavy duty hose for water discharge in industrial and construction applications, is strong and rolls up flat for easy storage. Reinforcement includes three spiral plies and longitudinal synthetic cords for excellent burst resistance. Commonly provided with cam and groove or threaded coupling fittings and hose nozzles.

Temperature range is -5F to 170F. Pressure rating drops if over 110F.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	WEIGHT	COIL LENGTHS
	(in)	(in)		(psi)	(lbs/100ft)	(ft)
	1 1/2			150	24	300
	2			150	30	300
	2 1/2			150	40	300
	3			150	53	300
	4			150	77	300
	6			150	125	300
	8			115	190	300

**NOTES:**

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <p><b>HOSECRAFT USA</b></p>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;"><b>PD2</b></td> </tr> <tr> <td>DRAWN BY: PDB 1/1/04</td> <td style="text-align: center;"><b>PVC HEAVY DUTY DISCHARGE</b></td> </tr> </table>	MODEL:	<b>PD2</b>	DRAWN BY: PDB 1/1/04	<b>PVC HEAVY DUTY DISCHARGE</b>
MODEL:	<b>PD2</b>				
DRAWN BY: PDB 1/1/04	<b>PVC HEAVY DUTY DISCHARGE</b>				