PH1 MATERIAL HANDLING HOSE



The Model PH1 is a high quality, heavy duty SBR rubber blended with static carbon black and rigid PVC helix material handling hose. It provides quiet operation, excellent bendability, and good abrasion resistance that has a smooth bore. It is made for transferring and suction of dry materials, and dissipates static.

PHONE: 800-584-4168 FAX: 312-421-6327

Commonly provided with cam and groove, flange, and other fittings.

Temperature range is -40F to 140F.

| QT Y | INNER DIA | OAL | FITTINGS | OUTER DIA | PRESS* | VAC* | BEND RADIUS | WEIGHT |
|---------|--------------|------|----------|-----------|--------|---------|----------------|----------|
| Ť | (in) | (in) | | (in) | (psi) | (in Hg) | (in) | (lbs/ft) |
| | 1 1/2 | | | 1 13/16 | 45 | FULL | 2 | 0.42 |
| | 2 | | | 2 3/8 | 40 | FULL | 3 | 0.59 |
| | 2 1/2 | | | 2 7/8 | 35 | FULL | 3 | 0.80 |
| | 3 | | | 3 1/2 | 35 | FULL | 4 | 1.18 |
| | 4 | | | 4 5/8 | 30 | FULL | 6 | 1.95 |
| | 5 | | | 5 3/8 | 30 | 28 | 10 | 2.42 |
| | 6 | | | 6 3/4 | 30 | 28 | 12 | 3.50 |
| | 8 | | | 9 | 30 | 28 | 18 | 5.91 |
| | 10 | | | 11 1/4 | 28 | 25 | - | - |
| | 12 | | | 13 3/8 | 25 | 25 | - | - |

NOTES: *THE HOSE IS RATED FOR 0 TO 140 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RATING.

| CUSTOMER | | → HOSECRAFT |
|---------------|------------------------|-------------------------------|
| PROJECT | | USA |
| ENGINEER | | |
| CONTRACTOR | MODEL: | PH1 |
| CERTIFICATION | DRAWN BY: PDB 8/04 | PVC MATERIAL HANDLING HOSE |