

PM1 MULTIPURPOSE AIR HOSE




A hybrid thermoplastic hose that provides durability and flexibility, is lightweight and has a low drag resistance. F5™ is non-marking, oil resistant and performs well under cold temperatures to -40°F. This 300 PSI hose is designed for a variety of pneumatic applications in industries such as construction and manufacturing. ARPM Class B, polyester yarn reinforced.

Temperature range is -15F to 150F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	1/4			0.50	300	0.08	0.06
	5/16			0.59	300	0.10	0.09
	3/8			0.64	300	0.13	0.10
	1/2			0.81	300	0.17	0.16
	3/4			1.11	300	0.28	0.26
	1			1.37	300	0.37	0.35

NOTES: THE HOSE IS RATED FOR -40 TO 158 DEG F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____							
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;">PM1</td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;">MULTIPURPOSE PVC</td> </tr> <tr> <td style="text-align: center;">PDB 1/1/04</td> <td></td> </tr> </table>	MODEL:	PM1	DRAWN BY:	MULTIPURPOSE PVC	PDB 1/1/04	
MODEL:	PM1						
DRAWN BY:	MULTIPURPOSE PVC						
PDB 1/1/04							