

## PN1 PVC SUCTION HOSE




PN1 is a lightweight PVC suction hose used for countless industrial and construction liquid and material applications where only mild chemical resistance is required. It is more economical and much lighter than similar rubber hoses, and has a smooth bore.

15F to 150F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE*	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	1			1.27	90	3	0.3
	1 1/4			1.53	90	4	0.4
	1 1/2			1.82	90	5	0.5
	2			2.36	70	6	0.7
	2 1/2			2.98	65	8	1
	3			3.44	55	9	1.25
	4			4.52	50	13	1.9
	6			6.80	45	24	4.6
	8			8.95	40	35	7.15
	10			11.34	40	41	12.37
	12			13.39	35	53	15.66

**NOTES:** \*THE HOSE IS RATED FOR -4 TO 150 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RATING.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <p style="font-size: 24px; font-weight: bold; color: red; margin: 0;">HOSECRAFT USA</p>						
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;"><b>PN1</b></td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;"><b>PVC SUCTION HOSE</b></td> </tr> <tr> <td style="text-align: center;">PDB 8/04</td> <td></td> </tr> </table>	MODEL:	<b>PN1</b>	DRAWN BY:	<b>PVC SUCTION HOSE</b>	PDB 8/04	
MODEL:	<b>PN1</b>						
DRAWN BY:	<b>PVC SUCTION HOSE</b>						
PDB 8/04							