PT2 CLEAR PVC TUBING



PT2 is a crystal clear unreinforced PVC tubing with a mirrorsmooth finish. It's smooth interior provides excellent flow characteristics. It's applications are varied, and include a variety of weak chemicals, gases, as well as food products and is easily flushed and cleaned.

- Made of FDA approved materials

TEMPERATURE RANGE: 25F to 130F.

QTY	INNER DIA	OUTER DIA.	FITTINGS	OPERATING PRESSURE	COIL LENGTH	COIL WEIGHT
	(in)	(in)		(psi)	(ft)	(lbs)
	1/8	1/4		65	100	2.65
	3/16	5/16		55	100	3.07
	1/4	3/8		50	100	3.40
	1/4	7/16		60	100	5.38
	1/4	1/2		70	100	8.37
	5/16	7/16		40	100	4.63
	5/16	1/2	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	50	100	7.16
	3/8	1/2		35	100	5.58
	3/8	9/16	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	50	100	8.18
	3/8	5/8	hannananananananananananananananananana	60	100	11.55
	1/2	5/8		30	100	7.39
	1/2	3/4	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>	45	100	13.14
	9/16	7/8		45	100	18.73
	5/8	7/8		40	100	15.81
	3/4	1	hannananananananananananananananananana	35	100	18.60
	7/8	1-1/8		30	100	21.10
	1	1-1/4		25	100	23.80
	1-1/4	1-3/4		50	50	33.60
	1-1/2	2		35	50	42.90
	2	2-3/8	10000000000000000000000000000000000000	25	50	38.20

NOTES: *THE HOSE IS RATED FOR 25 TO 130 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RAT

CUSTOMER

LICCECT A ET

PROJECT_____

ENGINEER _____

CONTRACTOR

CERTIFICATION ____

MODEL: PT2

| DRAWN BY: | CLEAR PVC | 10/22/2018

PHONE: 800-584-4168 FAX: 312-421-6327