

## RB1 SAND BLAST HOSE



RB1 is used for conducting sand, steel, shot or other abrasives at high velocity, often in conjunction with blasting, cleaning or finishing stone, metal, and other surfaces. Construction consists of thick plies of an abrasion resistant, static-conducting tube, with a black abrasion resistant cover. Used with OD mounted sand blast couplings.

25F to 180F.

QTY	NOMINAL DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	<b>1/2</b>			1 1/16	150	2	0.37
	<b>3/4</b>			1 1/2	150	4	0.71
	<b>1</b>			1 7/8	150	4	0.93
	<b>1 1/4</b>			2 5/32	150	4	1.11
	<b>1 1/2</b>			2 13/32	150	4	1.23
	<b>2</b>			2 7/8	150	4	1.48

**NOTES:**

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;"><b>RB1</b></td> </tr> <tr> <td style="width: 50%;">DRAWN BY: PDB 1/1/04</td> <td style="width: 50%; text-align: center;"><b>SAND BLAST</b></td> </tr> </table>	MODEL:	<b>RB1</b>	DRAWN BY: PDB 1/1/04	<b>SAND BLAST</b>
MODEL:	<b>RB1</b>				
DRAWN BY: PDB 1/1/04	<b>SAND BLAST</b>				