

## RC2 EXTRA FLEX CHEMICAL HOSE



The Model RC2 Gamma top quality UHMW chemical suction/discharge hose with corrugations for superior flexibility and dual helix construction. For transfer of corrosive chemicals, acids, fuels and other chemicals.

-40 deg F to 250 deg F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	<b>1</b>			1 1/2	200	2	0.57
	<b>1 1/2</b>			2 1/32	200	3	0.81
	<b>2</b>			2 9/16	200	4	1.11
	<b>2 1/2</b>			3 1/8	200	5	1.4
	<b>3</b>			3 5/8	200	6	1.77
	<b>4</b>			4 5/8	200	8	2.83
	<b>6</b>			4 5/8	200	20	5.5

**NOTES:** THE HOSE IS RATED FROM -40F TO 225F.  
\*ALSO AVAILABLE IN ANY OTHER ELASTOMER.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____							
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;"><b>RC2</b></td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;"><b>EXTRA FLEX CHEMICAL HOSE</b></td> </tr> <tr> <td>PDB 1/1/04</td> <td></td> </tr> </table>	MODEL:	<b>RC2</b>	DRAWN BY:	<b>EXTRA FLEX CHEMICAL HOSE</b>	PDB 1/1/04	
MODEL:	<b>RC2</b>						
DRAWN BY:	<b>EXTRA FLEX CHEMICAL HOSE</b>						
PDB 1/1/04							