

RD6 SLIP RING / COUPLERS RUBBER WATER HOSE



This layflat water discharge hose is built with a male and female end enabling the user to connect hoses. The male end is inserted into the female end and locked into place with a steel ring.


Construction:

Tube: Black synthetic EPDM rubber
 Reinforcement: Multiple plies polyester tire cord

Cover: Black synthetic rubber
 Length: Standard lengths, 50 ft.
 Temperature Range: --40°F (-40°C) to +180°F (+82°C)

QTY	INNER DIA	OAL	PLIES	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(ft)		(in)		(psi)	
	4	50	2	4.22	100	N/A	40
	6	50	2	6.22	75	N/A	62
	8	50	2	8.22	65	N/A	79
	10	50	2	10.22	50	N/A	96
	12	50	2	12.20	40	N/A	120
	14	50	2	14.22	35	N/A	135
	16	50	2	16.22	35	N/A	163
	24	50	2	24.22	30	N/A	235

NOTES: IDEAL FOR DE-WATERING APPLICATIONS, IRRIGATION, AND LIGHT DREDGING. SOME LEAKING AT CONNECTIONS SHOULD BE EXPECTED.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 HOSE CRAFT USA
	MODEL: RD6
	DRAWN BY: LAY-FLAT WATER DISCHARGE PDB 7/1/19