RM2 MULTIPURPOSE HOSE - EPDM HOSE



RM2 is a good quality and economical multipurpose EPDM hose recommended for water and air, as well as many other industrial and construction uses (not suitable for petroleum products) up to 2" diameters. It is reinforced with textile cord and has excellent weather and abrasion resistance. -40F to 190F.

| QT Y | INNER DIA | OAL | FITTINGS | OUTER DIA | PRESSURE | BEND RADIUS | WEIGHT |
|---------|-----------|------|----------|-----------|----------|-------------|----------|
| | (in) | (in) | | (in) | (psi) | (in) | (lbs/ft) |
| | 1/4 | | | 1/2 | 200 | 1 1/2 | 0.09 |
| | 1/4 | | | 17/32 | 250 | 2 1/2 | 0.11 |
| | 1/4 | | | 17/32 | 300 | 3. 25 | 0.1 |
| | 5/16 | | | 5/8 | 200 | 3 1/4 | 0.12 |
| | 3/8 | | | 21/32 | 200 | 3 1/2 | 0.17 |
| | 3/8 | | | 23/32 | 250 | 3 1/2 | 0.17 |
| | 3/8 | | | 23/32 | 300 | 4 | 0.17 |
| | 1/2 | | | 13/16 | 200 | 4 1/2 | 0.2 |
| | 1/2 | | | 7/8 | 250 | 4 3/4 | 0.22 |
| | 1/2 | | | 7/8 | 300 | 4 3/4 | 0.22 |
| | 5/8 | | | 1 | 250 | 5 1/2 | 0.27 |
| | 3/4 | | | 1 5/32 | 250 | 5 3/4 | 0.35 |
| | 3/4 | | | 1 5/32 | 300 | 6 1/4 | 0.37 |
| | 1 | | | 1 7/16 | 200 | 6 1/2 | 0.54 |
| | 1 1/4 | | | 1 3/4 | 200 | 8 | 0.75 |
| | 1 1/2 | | | 2 | 200 | 10 | 0.86 |
| | 2 | | | 2 1/2 | 200 | 12 | 1.16 |

NOTES:

THE HOSE IS RATED FOR -40 TO 190 DEG F.

| CUSTOMER | K | - ▶ HOSECRAFT |
|---------------|---------------|------------------|
| PROJECT | RS | USA |
| ENGINEER | | |
| CONTRACTOR | MODEL: | RM2 |
| CERTIFICATION | DRAWN BY: | MULTIPURPOSE |
| | PDB 8/04 | HOSE - EPDM |

PHONE: 800-584-4168 FAX: 312-421-6327