RP1 PETROLEUM TRANSFER HOSE



The RP1 hose is the industry standard for suction ready in-plant, tank truck and general transfer of petroleum products at 150psi pressures. Handles gasoline, oil, and refined petroleum products to 55% aromatic content. Also available in ready made assemblies and higher pressures. 1-1/4" to 4" diameters. -40F to 180F. Also provided with a corrugated cover for extra flexibility (RP1C), and for 300psi service (RP1HP).

Temperature range is -25F to 180F.

QT Y	INNER DIA	OAL	FITTINGS	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in)	(lbs/ft)
	1 1/4			150	4	0.7
	1 1/2			150	6	0.84
	2			150	8	1.21
	2 1/2			150	10	1.48
	3			150	13	1.79
	4			150	19	2.64

NOTES: THE HOSE IS RATED FROM -40F TO 180F.

ALSO AVAILABLE IN CORRUGATED COVER AS RP1C.

CUSTOMER	 K	→ HOSECRAFT
PROJECT		USA
ENGINEER		
CONTRACTOR	 MODEL:	RP1
CERTIFICATION	 DRAWN BY:	PETROLEUM
	PDB 1/1/04	TRANSFER HOSE

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327