

RP1C PETROLEUM TRANSFER HOSE




The Model RP1C is similar to the RP1, but with a corrugated cover for extra flexibility. For suction or discharge use in plant operations and in tank trucks to transfer oil, gasoline, and other petroleum based products at 150psi and full vacuum. Nitrile tube and Neoprene cover.

Temperature range is -40F to 180F.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in)	(lbs/ft)
	1 1/2			150	1 1/2	0.77
	2			150	2	1.1
	3			150	3	1.6
	4			150	4	2.6
	6			150	8	4.2
	8			150	10	6.1

NOTES: THE HOSE IS RATED FROM -40F TO 180F.
ALSO AVAILABLE IN CORRUGATED COVER AS RP1C.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <p>HOSECRAFT USA</p>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">RP1C</td> </tr> <tr> <td>DRAWN BY: PDB 1/1/04</td> <td style="text-align: center;">PETROLEUM TRANSFER HOSE</td> </tr> </table>	MODEL:	RP1C	DRAWN BY: PDB 1/1/04	PETROLEUM TRANSFER HOSE
MODEL:	RP1C				
DRAWN BY: PDB 1/1/04	PETROLEUM TRANSFER HOSE				