

RP1HP 300PSI PETROLEUM TRANSFER HOSE




The Model RP1HP is for suction or discharge use in plant operations and in tank trucks to transfer oil, gasoline, and other petroleum based products at 300psi.

Available with a corrugated cover as the RP1HPC, and in a 150psi version as the RP1.

Nitrile tube and Neoprene cover.
Temperature range is -40F to 180F.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in)	(lbs/ft)
	1 1/2			300	10	0.84
	2			300	13	1.3
	2 1/2			300	16	1.65
	3			300	20	2.3
	4			300	28	3.85
	6			300	36	5.41

NOTES: THE HOSE IS RATED FROM -40F TO 180F.
ALSO AVAILABLE IN CORRUGATED COVER AS RP1HPC.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">RP1HP</td> </tr> <tr> <td>DRAWN BY: PDB 1/1/04</td> <td style="text-align: center;">300PSI PETROLEUM TRANSFER HOSE</td> </tr> </table>	MODEL:	RP1HP	DRAWN BY: PDB 1/1/04	300PSI PETROLEUM TRANSFER HOSE
MODEL:	RP1HP				
DRAWN BY: PDB 1/1/04	300PSI PETROLEUM TRANSFER HOSE				