

RP1HPC 300PSI PETROLEUM CORRUGATED COVER HOSE




The Model RP1HPC is similar to the RP1HP, but with a corrugated cover for better flexibility. For suction or discharge use in plant operations and in tank trucks to transfer oil, gasoline, and other petroleum based products at 300psi.

Nitrile tube and Neoprene cover.
Temperature range is -40F to 180F.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in)	(lbs/ft)
	2			300	8	1.01
	3			300	12	1.46
	4			300	16	2.34

NOTES: THE HOSE IS RATED FROM -40F TO 180F.
ALSO AVAILABLE IN CORRUGATED COVER AS RP1HPC.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <p style="font-size: 24px; font-weight: bold; color: red; margin: 0;">HOSECRAFT USA</p>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;">RP1HPC</td> </tr> <tr> <td>DRAWN BY: PDB 1/1/04</td> <td style="text-align: center;">300PSI PETROLEUM TRANSFER HOSE</td> </tr> </table>	MODEL:	RP1HPC	DRAWN BY: PDB 1/1/04	300PSI PETROLEUM TRANSFER HOSE
MODEL:	RP1HPC				
DRAWN BY: PDB 1/1/04	300PSI PETROLEUM TRANSFER HOSE				