

RP3 HARDWALL GASOLINE CURB PUMP HOSE

For petroleum and gas dispensing from pumps desiring a hardwall construction for full flow.

Long service life and kink resistance are hallmarks of this hardwall hose, which consists of a RMA Class A, Type C Nitrile tube and high tensile steel wire braid helix reinforcement that prevents kinking or collapse in reel use. Highly resistant to cuts, abrasion, sun, and weather. UL 330 approved.


The fittings on the assemblies are internally expanded, chrome plated NPT threads. One of the fittings can be provided as a swivel if wanted. Recommended for all unleaded or leaded gasoline, diesel, up to E15 Ethanol, and B-20 Biodiesel. All hoses are 100% pressure tested, and inspected for electrical continuity.

Special lengths are available up to 500 feet. Contact factory. Temperature range is -40F to 120F.



QTY	INNER DIA	OUTER DIA	PRESSURE	BRAID	OAL
	(in)	(in)	(psi)		(in)
	5/8	NA	350	1	
	3/4	NA	250	1	
	1	NA	150	2	

NOTES:

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____							
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">RP3</td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;">GASOLINE CURB PUMP HOSE</td> </tr> <tr> <td style="text-align: center;">PDB 8/04</td> <td></td> </tr> </table>	MODEL:	RP3	DRAWN BY:	GASOLINE CURB PUMP HOSE	PDB 8/04	
MODEL:	RP3						
DRAWN BY:	GASOLINE CURB PUMP HOSE						
PDB 8/04							