

## RP9 HOT TAR & ASPHALT HOSE



The Model RP9 is designed to handle high temperature petroleum based materials, including asphalt, tar, oil and others.


It is reinforced with a dual wire helix, appropriate for suction service, and has an abrasion and weather resistant cover, and a premium grade tube.

Normally provided with internally expanded fittings.

Temperature range is -40F to 350F, intermittent service.

QTY	INNER DIA	OAL	FITTINGS	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in)	(lbs/ft)
	2			150	5	1.20
	2 1/2			150	6	1.70
	3			150	7	2.00
	4			150	10	2.50

**NOTES:** THE HOSE IS RATED FROM -40F TO 350F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <b>HOSECRAFT USA</b>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">MODEL:</td> <td style="text-align: center;"><b>RP9</b></td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;"><b>HOT TAR &amp; ASPHALT HOSE</b></td> </tr> </table>	MODEL:	<b>RP9</b>	DRAWN BY:	<b>HOT TAR &amp; ASPHALT HOSE</b>
MODEL:	<b>RP9</b>				
DRAWN BY:	<b>HOT TAR &amp; ASPHALT HOSE</b>				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 30%;">PDB 1/1/06</td> <td></td> </tr> </table>	PDB 1/1/06			
PDB 1/1/06					