## **RT1 STEAM HOSE**



RT1 is a rubber steam hose with a heat resistant EPDM tube and cover for maximum life. It is used for cleaning, thawing, steam pumps, heat control, and many other all around steam applications. Usually used with ground joint fittings. Also available in Butyl.

PHONE: 800-584-4168 FAX: 312-421-6327

-20F to 415F.

QT Y	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
'	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	1/2			1	250	-	0.4
	3/4			1 1/4	250	-	0.49
	1			1 5/8	250	-	0.78
	1 1/4			1 15/16	250	-	0.83
	1 1/2			2 1/8	250	-	1.03
	2			2 3/4	250	-	1.88
	3			3 11/16	250	-	2.73

**NOTES:** THE HOSE IS RATED FROM -20F TO 415F. ALSO AVAILABLE IN ANY OTHER ELASTOMER.

CUSTOMER PROJECT ENGINEER		HOSECRAFT
CONTRACTOR	MODEL:	RT1
CERTIFICATION	 DRAWN BY: PDB 1/1/04	RUBBER STEAM HOSE