## **RU1-AS PRESSURE WASHER HOSE ASSEMBLY**



The Hosecraft USA RU1-AS Pressure Washer Hoses are available in three grades/colors of gray, black, and blue, and are 3/8" diameters. Normally used on pressure wash machines with working pressures up to 4000psi and 5800psi.

These quality power wash hoses feature a unique cover compound, excellent for abrasion and ozone resistance. The synthetic rubber tubes are resistant to cold and hot water with usual cleaning agents. The hoses are reinforced with a braid of high tensile steel wire, and are coupled with Hydraulic 100R1 type crimping specifications.

Available in bulk, 50 ft, 100 ft, and custom lengths (contact factory).

15F to 310F temperature rating

For use on pressure washer machines with working pressures up to 4000 psi and Application:

temperatures up to 310°F.

Tube: Synthetic rubber, resistant against cold and hot water with usual cleaning agents.

Reinforcement: One braid of high tensile steel wire.

> Cover: Abrasion and ozone resistant synthetic rubber, wrapped or smooth.

Temperature: 14°F to 310°F

500 ft 2 piece reels or cut-to-length coils Packaging:

Hydraulic 100R1 type crimped to fitting manufacturer specifications Couplings:

Colors: Blue, Gray, Black

## Features:

- Available in bulk, 50 ft., 100 ft., and custom lengths
- Lightweight and easy to handle
- A unique cover compound gives JGB Eaglewash I hoses the durability and flexibility to handle abrasion and normal cleaning chemicals used in the wash industry.

Part #			Nom. ID	OD	Bend Radius	Min Burst	Max. Oper. Pressure	Weight
Black	Blue	Grey	in	in	in	psi	psi	lbs/ft
168-6006-30011	168-0066-40001	168-0067-40001	3/8	.63	2.95	12,000	4000	.188

CUSTOMER HOSECRAFT **PROJECT ENGINEER** CONTRACTOR MODEL: RU1-AS CERTIFICATION DRAWN BY: PRESSURE **WASHER HOSE** PDB 1/1/17 PHONE: 800-584-4168 FAX: 312-421-6327