

RV2 OVER THE PIPE HOSE



RV2 suction ready hose can slip over piping outer diameters for a sleeve fit and is available in a wide range of diameters.

It is constructed of an oil, gasoline and heat resistant black Nitrile tube and Neoprene cover with a 2-ply, Nylon mesh / helical wire reinforced construction

Meets SAE J1527 TYPE A2, USCG 1942F and SAEJ2006R2 for marine exhaust hose.

-20F to 212F. Not for steam service.
Rated for full vacuum

12 ft and 60 ft lengths readily available

QTY	Dia	Outer Dia	Lngh-ft	Press	Bend R	Wt.	Product No.
	(in)	(in)	(ft)	(psi)	(in)	(lbs)	
	1/2	0.88	12	60	2	3.84	HOSE-RV2-12-0050
	5/8	1	12	60	2	4.32	HOSE-RV2-12-0062
	3/4	1.13	12	58	3	5.76	HOSE-RV2-12-0075
	7/8	1.25	12	55	3	6.6	HOSE-RV2-12-0087
	1	1.38	12	53	3	7.32	HOSE-RV2-12-0100
	1 1/8	1.5	12	50	3	8.04	HOSE-RV2-12-0112
	1 1/4	1.63	12	44	3	8.64	HOSE-RV2-12-0125
	1 3/8	1.75	12	44	4	9.48	HOSE-RV2-12-0137
	1 1/2	1.88	12	44	4	10.08	HOSE-RV2-12-0150
	1 5/8	2	12	41	5	10.8	HOSE-RV2-12-0162
	1 3/4	2.13	12	41	5	11.52	HOSE-RV2-12-0175
	1 7/8	2.25	12	38	5	12.24	HOSE-RV2-12-0187
	2	2.38	12	35	6	12.84	HOSE-RV2-12-0200
	2 1/8	2.5	12	34	6	13.56	HOSE-RV2-12-0212
	2 1/4	2.63	12	34	6	14.16	HOSE-RV2-12-0225
	2 3/8	2.75	12	33	7	14.28	HOSE-RV2-12-0237
	2 1/2	2.88	12	30	8	14.76	HOSE-RV2-12-0250
	2 5/8	3	12	30	10	15.36	HOSE-RV2-12-0262
	2 3/4	3.13	12	29	10	16.08	HOSE-RV2-12-0275
	2 7/8	3.25	12	29	11	16.8	HOSE-RV2-12-0287
	3	3.38	12	26	13	18.12	HOSE-RV2-12-0300
	3 1/2	3.88	12	20	14	21	HOSE-RV2-12-0350
	4	4.38	12	18	15	23.76	HOSE-RV2-12-0400
	4 1/2	4.88	12	16	16	26.52	HOSE-RV2-12-0450
	5	5.38	12	14	28	32.8	HOSE-RV2-12-0500
	5 1/2	5.88	12	13	31	35.8	HOSE-RV2-12-0550
	6	6.38	12	11	33	41.04	HOSE-RV2-12-0600



MODEL:

RV2

DRAWN BY:

TDV 6/26/19

**OVER THE PIPE
HOSE WITH WIRE**

RV2 OVER THE PIPE HOSE

RV2 OVER THE PIPE HOSE



RV2 suction ready hose can slip over piping outer diameters for a sleeve fit and is available in a wide range of diameters.

It is constructed of an oil, gasoline and heat resistant black Nitrile tube and Neoprene cover with a 2-ply, Nylon mesh / helical wire reinforced construction

Meets SAE J1527 TYPE A2, USCG 1942F and SAEJ2006R2 for marine exhaust hose.

-20F to 212F. Not for steam service.
Rated for full vacuum

12 ft and 60 ft lengths readily available

QTY	Dia	Outer Dia	Length-ft	Press	Bend R	Wt.	Product No.
	(in)	(in)	(ft)	(psi)	(in)	(lbs)	
	1/2	0.88	60	60	2	19.2	HOSE-RV2-60-0050
	5/8	1	60	60	2	21.6	HOSE-RV2-60-0062
	3/4	1.13	60	58	3	28.8	HOSE-RV2-60-0075
	7/8	1.25	60	55	3	33	HOSE-RV2-60-0087
	1	1.38	60	53	3	36.6	HOSE-RV2-60-0100
	1 1/8	1.5	60	50	3	40.2	HOSE-RV2-60-0112
	1 1/4	1.63	60	44	3	43.2	HOSE-RV2-60-0125
	1 3/8	1.75	60	44	4	47.4	HOSE-RV2-60-0137
	1 1/2	1.88	60	44	4	50.4	HOSE-RV2-60-0150
	1 5/8	2	60	41	5	54	HOSE-RV2-60-0162
	1 3/4	2.13	60	41	5	57.6	HOSE-RV2-60-0175
	1 7/8	2.25	60	38	5	61.2	HOSE-RV2-60-0187
	2	2.38	60	35	6	64.2	HOSE-RV2-60-0200
	2 1/8	2.5	60	34	6	67.8	HOSE-RV2-60-0212
	2 1/4	2.63	60	34	6	70.8	HOSE-RV2-60-0225
	2 3/8	2.75	60	33	7	71.4	HOSE-RV2-60-0237
	2 1/2	2.88	60	30	8	73.8	HOSE-RV2-60-0250
	2 5/8	3	60	30	10	76.8	HOSE-RV2-60-0262
	2 3/4	3.13	60	29	10	80.4	HOSE-RV2-60-0275
	2 7/8	3.25	60	29	11	84	HOSE-RV2-60-0287
	3	3.38	60	26	13	90.6	HOSE-RV2-60-0300
	3 1/2	3.88	60	20	14	105	HOSE-RV2-60-0350
	4	4.38	60	18	15	118.8	HOSE-RV2-60-0400
	4 1/2	4.88	60	16	16	132.6	HOSE-RV2-60-0450
	5	5.38	60	14	28	164	HOSE-RV2-60-0500
	5 1/2	5.88	60	13	31	179	HOSE-RV2-60-0550
	6	6.38	60	11	33	205.2	HOSE-RV2-60-0600



MODEL:

RV2

DRAWN BY:

TDV 6/26/19

**OVER THE PIPE
HOSE WITH WIRE**