

TD14 FLAME RETARDANT HVAC DUCT HOSE




The Model TD14 is a quality single ply silver PVC coated fiberglass fabric hose crimped to a metal clip. It is ideal for HVAC applications, with all flame retardant materials qualified to UL 181, Class 1, and UL 94V-0. Other applications include A/C ventilation, heaters, smoke ejectors, and many fume and ventilation uses.

The hose is extremely flexible, and the metal strip acts as a protective wearstrip. Standard diameter sizes are 3" to 14", but other sizes are available on request. Standard lengths are 25 feet, but other lengths are available.

The temperature range is 20F to 250F.

QTY	HOSE DIA	OAL	WT/FT	PRESSURE	VACUUM	BEND RADIUS	STANDARD LENGTHS
	(in)	(feet)	(lbs)	(PSI)	(in Water)	(in)	(feet)
	3		0.39	12	5	2.5	25
	4		0.48	9	4	3.0	25
	5		0.56	5.5	3.5	3.5	25
	6		0.64	4.5	3.2	4.0	25
	7		0.72	4	3	5.0	25
	8		0.80	3.8	2.8	5.5	25
	9		0.90	3.2	2.5	6.3	25
	10		1.00	3	2	7.0	25
	12		1.15	2.5	1.8	8.5	25
	14		1.25	2	1.5	10.0	25

NOTES: THE HOSE IS RATED FOR 20F TO 250F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 60%;">MODEL:</td> <td style="text-align: center;">TD14</td> </tr> <tr> <td>DRAWN BY: PDB 1/1/06</td> <td style="text-align: center;">FLAME RETARDANT HVAC DUCT HOSE</td> </tr> </table>	MODEL:	TD14	DRAWN BY: PDB 1/1/06	FLAME RETARDANT HVAC DUCT HOSE
MODEL:	TD14				
DRAWN BY: PDB 1/1/06	FLAME RETARDANT HVAC DUCT HOSE				