


TD5 THERMOPLASTIC POLYURETHANE HEAVY SERVICE




The TD5 hose is a clear thermoplastic polyurethane hose. It is very well suited for leaf and lawn collection, as well as other material handling applications requiring both light weight and abrasion resistance. Extremely flexible, but heavier wall at .030" than other hoses of its type. FDA acceptable.

Diameters from 2" to 24".

Temperature range -65F to 225F.

QTY	HOSE DIA	OAL	FITTINGS	PRESSURE	VACUUM	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in Hg)	(in)	(lbs/FT)
	2			30	29	2	0.25
	2 1/2			30	29	2 1/2	0.32
	3			29	29	3	0.4
	4			25	29	4	0.7
	5			22	17	5	0.9
	6			19	15	6	1.0
	7			16	12	7	1.2
	8			14	9	8	1.5
	10			11	4	8	1.6
	12			10	2.2	10	2.0
	14			8	3.3	12	2.5
	16			7	2.2	147	3.0
	18			6	1.4	16	3.3
	20			5.5	1	18	3.7
	22			5	0.9	20	4.1
	24			4	0.75	22	4.5

NOTES: THE COMPRESSION RATION IS 3:1
THE WALL THICKNESS IS .045"

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">TD5</td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;">THERMOPLASTIC POLYURETHANE HEAVY SERVICE</td> </tr> </table>	MODEL:	TD5	DRAWN BY:	THERMOPLASTIC POLYURETHANE HEAVY SERVICE
MODEL:	TD5				
DRAWN BY:	THERMOPLASTIC POLYURETHANE HEAVY SERVICE				
	PDB 1/1/04				