

TD8 FLAME RETARDANT AIR VENT HOSE




The Model TD8 is an economical air ventilation, fume removal flame retardant hose with vinyl coated woven fiberglass cover permanently bonded to a PVC coated spring steel wire helix. This hose meets UL 181 class flammability ratings and NFPA 90A-90B fire code. It is ideal for low volume air transfer and applications include dry cleaning equipment, air intake and exhaust ducts, heating and cooling systems, dust, and many others.

Temperature range is 0F to 250F.

| QTY | HOSE DIA | OAL | FITTINGS | PRESSURE | VACUUM | BEND RADIUS | STANDARD LENGTHS |
|-----|----------|------|----------|------------|------------|-------------|------------------|
| | (in) | (in) | | (in Water) | (in Water) | (in) | (feet) |
| | 2 | | | 16 | 1 | 2 | 25 |
| | 3 | | | 16 | 1 | 3 | 25 |
| | 4 | | | 16 | 1 | 4 | 25 |
| | 5 | | | 16 | 1 | 5 | 25 |
| | 6 | | | 16 | 1 | 6 | 25 |
| | 7 | | | 16 | 1 | 7 | 25 |
| | 8 | | | 16 | 1 | 8 | 25 |
| | 9 | | | 16 | 1 | 9 | 25 |
| | 10 | | | 16 | 1 | 10 | 25 |
| | 12 | | | 16 | 1 | 12 | 25 |
| | 14 | | | 16 | 1 | 14 | 25 |
| | 16 | | | 16 | 1 | 16 | 15 |
| | 18 | | | 16 | 1 | 18 | 15 |
| | 20 | | | 16 | 1 | 20 | 15 |

NOTES: THE HOSE IS RATED FOR -40F TO 250F.

| | | | | | |
|--|---|--------|------------|-----------|--|
| CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____ |  | | | | |
| | <table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">TD8</td> </tr> <tr> <td>DRAWN BY:</td> <td style="text-align: center;">FLAME RETARDANT AIR VENTILATION</td> </tr> </table> | MODEL: | TD8 | DRAWN BY: | FLAME RETARDANT AIR VENTILATION |
| MODEL: | TD8 | | | | |
| DRAWN BY: | FLAME RETARDANT AIR VENTILATION | | | | |
| | PDB 1/1/06 | | | | |