



## ENGINEERING & TECHNICAL DATA — TL1 HOSE

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.09	.020	1	1.75:1	29	55
1	.12	.022	1.7	2:1	29	45
1.25	.17	.024	1.5	2:1	29	35
1.375	.2	.026	1.4	2.25:1	29	35
1.5	.22	.026	1.5	2:1	29	35
1.75	.25	.026	2	2:1	27	30
2	.32	.026	2.2	2:1	27	28
2.25	.37	.030	2.5	1.9:1	25	25
2.5	.4	.030	3.1	2:1	26	25
3	.5	.030	3.7	2:1	22	18
4	.72	.032	4	2:1	14	16
5	.92	.035	5.25	2:1	12	17
6	1.11	.035	6.25	2:1	10	12
7	1.32	.035	7	2:1	10	11
8	1.5	.035	8	2:1	6	10
9	1.65	.040	9.25	2:1	5	9
10	1.85	.040	9.5	2:1	4	7
12	2.8	.040	10	3:1	4	5


Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Medium weight coextruded PVC hose with a rigid external PVC helix

**Temperature Range:** 20°F to 160°F

**Standard Color:** Clear with Black Helix

**Standard Lengths:** 12 & 25 Feet (Available in 100' lengths up to 6" ID.)



## ENGINEERING & TECHNICAL DATA — TL2 HOSE

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.09	.020	1	1.7:1	29	55
1	.13	.022	1.4	1.8:1	29	50
1.25	.17	.025	1.6	1.9:1	29	45
1.375	.02	.025	1.7	1.5:1	29	42
1.5	.22	.026	2	1.5:1	29	40
1.75	.3	.030	2.5	1.5:1	28	38
2	.34	.032	2.8	1.5:1	28	37
2.25	.37	.032	3.2	1.5:1	28	36
2.5	.4	.032	3.7	1.5:1	28	35
3	.46	.033	3.7	1.7:1	26	32
4	.75	.033	6	1.5:1	20	28
5	.83	.033	5.5	2:1	16	23
6	.92	.035	6.5	2:1	10	24
7	1.16	.035	7.5	2:1	9	21
8	1.32	.035	8.5	2:1	8	22
9	1.53	.040	9.25	2:1	7	20
10	1.65	.040	9.5	2.25:1	6	16
12	2.2	.040	10	3:1	5	10

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Medium weight coextruded thermoplastic polyurethane hose with a rigid external ABS helix

**Temperature Range:** -40°F to 200°F

**Standard Color:** Clear with Yellow Helix

**Standard Lengths:** 12 & 25 Feet (Available in 100' lengths up to 6" ID.)