TR2 RUBBER COVERED FEP HOSE



TR2 is a rubber covered, smooth bore FEP hose, available up to 3" diameters. It handles a very broad range of chemicals and has an abrasion, weather, and ozone resistant blue EPDM cover. Other colors available.

It is reinforced with a high strength textile and helix wire.

It is used in countless tough chemical, pharmaceutical and sanitary applications. Meets or exceeds requirements of FDA & USDA under 21 CRF 177.

-40F to 300F.

Q TY	HOSE DIA	OAL	FITTINGS	PRESSURE	VACUUM	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in Hg)	(in)	(lbs/ft)
	1/2			500	FULL	3	0.35
	3/4			500	FULL	4	0.5
	1			450	FULL	7	0.6
	1 1/2			350	FULL	10	0.9
	2			300	FULL	14	1.45

NOTES: THE HOSE IS RATED FOR -40 F TO 300 F.
OUTER COLOR OF HOSE MAY BE DIFFERENT THAN SHOWN.

CUSTOMER PROJECT ENGINEER	HOSECRAFT USA		
CONTRACTOR	MODEL:	TR2	
CERTIFICATION	DRAWN BY:	RUBBER COVERED FEP	
	PDB 3/7/12	HOSE	

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327