


TS1 BRAIDED PTFE SMOOTH BORE HOSE



TS1 is a smooth bore PTFE hose with a stainless steel braiding, available up to 2" diameters. It is lightweight, and handles a very broad range of chemicals at relatively high temperatures and pressures, and will not deteriorate in service.


It is used applications where continual large bending is not required.

-65F to 450F.

QTY	HOSE DIA	OAL	FITTINGS	PRESSURE	VACUUM	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in Hg)	(in)	(lbs/in)
	3/16			3000	26	2.0	0.047
	1/4			3000	26	2.0	0.077
	5/16			3000	26	3.0	0.098
	3/8			2500	26	4.0	0.11
	7/16			2250	26	4.5	0.124
	1/2			2000	26	5.2	0.124
	5/8			1500	26	6.5	0.154
	3/4			1200	26	7.7	0.17
	7/8			1100	26	8.2	0.198
	1			1000	20	9.0	0.273
	1 1/8			900	20	10.0	0.305
	1 1/4			750	20	16.0	0.35

NOTES:

SPECIAL HIGH PRESSURE ASSEMBLIES ARE ALSO AVAILABLE.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 <p style="font-size: 1.2em; font-weight: bold; color: red; margin: 0;">HOSECRAFT USA</p>				
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;">MODEL:</td> <td style="width: 50%; text-align: center; padding: 5px;">TS1</td> </tr> <tr> <td style="padding: 5px;">DRAWN BY: PDB 1/1/04</td> <td style="text-align: center; padding: 5px;">BRAIDED PTFE HOSE</td> </tr> </table>	MODEL:	TS1	DRAWN BY: PDB 1/1/04	BRAIDED PTFE HOSE
MODEL:	TS1				
DRAWN BY: PDB 1/1/04	BRAIDED PTFE HOSE				