UD2 TPU FUEL & CHEMICAL LAYFLAT HOSE



Compatible with the following fuels:

- MIL-DTL-83133 (JP-8) (NATO F-34),
- MIL-DTL-5624 (JP-5) (NATO F-44),
- A-A-52557 (Diesel-military (Also NATO F-54),
- ASTM D 975 (Diesel-US commercial),
- MIL-DTL-83133 (NATO F-35),
- ASTM D 1655 (Jet A-1),
- AFLP-3747 (NATO F-24)

Overview: The The Model UD2 is a premium quality thermoplastic polyether polyurethane (TPU) lay-flat discharge hose for fuels and other flamable liquids. It is designed as light and compact hose for the harshest abrasion and chemical environments. Available with an optional encapsulated anti-static discharge wire for flamable liquids. Special high tenacity polyester yarn with a circular woven weave results in high tensile strength and low elongation. Available in 2" to 6" diameters.

Features:

- Suitable for flamable liquids with the optional antistatic wire (< 1.5ohms/linear foot resistance)
- Extremely tough for the harshest environments
- Up to 660 foot continuous lengths
- Easy to deploy
- · Lightweight and rolls up compactly
- Very smooth inside for minimum friction loss and easy dragging.
- Quite flexible and resistant to vibration
- Certified for NSF 61 potable drinking water
- Meets military specification MIL-PRF-370K-A/C

QTY	INNER DIA	OAL	FITTINGS	WORKING PRESSURE	BURST PRESSURE	WALL THK	WEIGHT
	(in)	(ft)		(psi)	(psi)	(lbs/ft)	(lbs/ft)
	2			300	900	0.10	0.39
	3			250	750	0.13	0.58
	4			200	600	0.13	0.83
	6			225	675	0.13	1.38

CUSTOMER PROJECT ENGINEER		HOSECRAFT USA
CONTRACTOR	 MODEL:	UD2
CERTIFICATION	 DRAWN BY: PDB 1/1/08	POLYURETHANE FUEL & CHEMICAL LAYFLAT

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327