

UT1 CLEAR FABRIC REINFORCED POLYURETHANE TUBING




The Model UT1 is a clear polyurethane polyester yarn braid reinforced tubing with excellent abrasion resistance.

Applications are varied, and include food/potable water applications as well as some oils, greases, and fuels.

FDA, USDA, 3A and NSF61 grade. -90F to 175F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	COIL LENGTH	WEIGHT
	(in)	(ft)		(in)	(psi)	(feet)	(per reel)
	1/4			.47	250	100	0.04
	3/8			.63	200	100	0.1
	1/2			.75	150	100	0.13
	5/8			.905	125	100	0.15
	3/4			1.025	100	100	0.18
	1			1.3	75	100	0.25

NOTES: *THE HOSE IS RATED FOR -90 TO 175 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RATING.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 HOSECRAFT USA
	MODEL: UT1
	DRAWN BY: PDB 8/04
	CLEAR FABRIC REINFORCED POLYURETHANE

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60612

PHONE: 800-584-4168 FAX: 312-421-6327