

VB1 UTILITY BLOWER HOSE



The VB1 is a lightweight, one ply polyester-vinyl laminate, with expanded pitch with optional wearstrip, and is highly compressible. For positive pressure movement of air, dust and fumes at temperatures under 180 degrees F (intermit. to 225 degrees). Not for vacuum.

Standard lengths are 25 feet, but custom lengths are available. Can be secured with clamps on standard ends or provided with sewn cuffs, or belted cuffs, or ring connectors. Flame retardant to UL94V-O rating.

QTY	HOSE DIA	OAL	COMPR RATIO	PRESSURE	NEGATIVE PRESS	BEND RADIUS	WEIGHT
	(in)	(in)		(psi)	(in/hg)		(in)
	4		10:1	13	9	2.0	0.25
	5		10:1	12	7	3.1	0.32
	6		11:1	11	3.5	3.0	0.3
	8		11:1	8	2.8	4.5	0.45
	10		11:1	7	2	5.5	0.6
	12		11:1	5	1	6.8	0.7
	14		11:1	5	0.75	8.0	0.8
	16		11:1	5	0.5	9.0	0.9
	18		11:1	4	0.4	10.0	1
	20		11:1	3	0.3	11.0	1.1
	22		11:1	3	0.2	12.5	1.3
	24		11:1	2	0.1	13.5	1.4

NOTES: THE HOSE IS RATED FOR -20F TO 180F (INTERM. TO 225 F).

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____					
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">VB1</td> </tr> <tr> <td>DRAWN BY: PDB 3/22/05</td> <td style="text-align: center;">UTILITY BLOWER POLYESTER-VINYL</td> </tr> </table>	MODEL:	VB1	DRAWN BY: PDB 3/22/05	UTILITY BLOWER POLYESTER-VINYL
MODEL:	VB1				
DRAWN BY: PDB 3/22/05	UTILITY BLOWER POLYESTER-VINYL				