


VB1-HT HIGH TEMPERATURE BLOWER HOSE



The Model VB1-HT is the high temperature version of our VB1 Utility Blower Hose. Flame retardant Polyester-Vinyl laminate resists UV, ozone, mildew, and is easily stored. It is available in diameters from 8" to 24", and in custom sizes to 60". End finishes include plain (shown above), sewn, belted, or expanded ring cuffs. Flame Retardant to UL94V-O. -20F to 325F.

QTY	HOSE DIA	OAL	ENDS	PRESSURE	STD LENGTH	BEND RADIUS	WEIGHT
	(in)	(ft)		(psi)	(ft)	(in)	(lbs/in)
	8			3	25	5.0	10
	10			2	25	6.0	15
	12			1.5	25	7.5	18
	14			1.2	25	8.5	20
	16			1	25	9.5	23
	18			0.8	25	10.5	28
	20			0.7	25	11.5	30
	24			0.55	25	14.0	35

NOTES: THE HOSE IS RATED FOR -20F TO 325F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 HOSECRAFT USA				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 60%;">MODEL:</td> <td style="width: 40%; text-align: center;">VB1-HT</td> </tr> <tr> <td>DRAWN BY: PDB 5/26/17</td> <td style="text-align: center;">HIGH TEMP BLOWER HOSE</td> </tr> </table>	MODEL:	VB1-HT	DRAWN BY: PDB 5/26/17	HIGH TEMP BLOWER HOSE
MODEL:	VB1-HT				
DRAWN BY: PDB 5/26/17	HIGH TEMP BLOWER HOSE				