

VB3 INSULATED BLOWER HOSE




SHOWN WITH SEWN CUFF

The Model VB3 is an insulated blower hose designed for temporary heating and cooling. It resists UV rays, ozone, and mildew, and can be easily stored as well. Made with flame retardant UL94V-O rating Polyester-Vinyl laminate, reinforced with a spring steel wire helix and external PVC wearstrip. 1" fiberglass insulation (R-Value=4). Compression Ratio is 5:1.

End finishes include standard, sewn, belt, or expanded cuffs. It is available in diameters from 6" to 24", and has optional wear strips. Temperature range is -20F to 180F.

QTY	HOSE DIA	OAL	COMPRESSION RATIO	PRESSURE	VACUUM	BEND RADIUS	WEIGHT
	(in)	(ft)		(psi)	(in Hg)	(in)	(lbs/ft)
	6		5:1	3.3	5.5	3.6	0.6
	8		5:1	2.5	6	4.7	0.9
	10		5:1	2	3	6.0	1.1
	12		5:1	1.7	1.8	8.0	1.3
	14		5:1	1.5	1.2	8.5	1.5
	16		5:1	1.3	0.8	9.6	1.7
	18		5:1	1.1	0.6	11.0	1.9
	20		5:1	0.9	0.4	12.0	2.1
	24		5:1	0.8	0.25	14.0	2.5

NOTES: THE HOSE IS RATED FOR -20F TO 180F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 HOSECRAFT USA
	MODEL: VB3
	DRAWN BY: INSULATED BLOWER HOSE PDB 5/26/17