## **VB5 DRYING & HEATING BLOWER HOSE**



High strength sewn polyurethane coated black polyester fabric hose for high performance in lower and higher temperatures. Chemical, fuel, and oil resistant, as well as tough construction for drying, heating, & dehumidification applications. Flame retardant to UL 94V-0. 12" to 24" diameters. -60F to 400F.

QT Y	HOSE DIA	OAL	ENDS	PRESSURE	COMPR RATIO	BEND RADIUS	WEIGHT
	(in)	(ft)		(psi)		(in)	(lbs/ft)
	12			7	6:1	9.0	0.9
	14			6	6:1	10.0	1
	16			5	6:1	11.0	1.1
	18			4.5	6:1	12.0	1.3
	20			3	6:1	13.0	1.4
	24			2	6:1	15.5	1.6

**NOTES:** THE HOSE IS RATED FOR -60F TO 400F.

CUSTOMER PROJECT ENGINEER	ROJECT		HOSECRAFT	
CONTRACTOR		MODEL:	VB5	
CERTIFICATION		DRAWN BY: PDB 5/26/17	PORTABLE HEATER DUCT HOSE	

HOSECRAFT USA 2315 W. HUBBARD ST, CHICAGO, IL 60611

PHONE: 800-584-4168 FAX: 312-421-6327